

# C44H Series, 330 – 440 VAC, 700 – 1,000 VDC, for PFC and AC Filter

## Overview

The C44H Series are a polypropylene metallized film with cylindrical aluminium can type filled with liquid resin, screw terminals, plastic deck and overpressure safety device.

## Applications

Typical applications include commutation, power factor correction and AC harmonic filtering.

## Benefits

- Overpressure safety device
- High peak current capability
- Long lifetime
- Self-healing




## Part Number System

C44H	L	G	P	6100	A	A	S	J
Series	Rated Voltage	Case & Fixing Bolt Code	Terminal Style	Capacitance Code (pF)	Internal Code	Internal Code		Tolerance
C44H = MKP Capacitors for AC filtering	L = 330 V <sub>rms</sub> K = 440 V <sub>rms</sub>	G = Cylindrical aluminum case with M12 bolt	P = M6 Threaded Posts R = M10 Threaded Posts	Digits 9-11 indicate the first three digits of the capacitance value. Digit 8 indicates the number of zeros to be added.	A = Standard Z = Special			J = 5% K = 10%

*It is not possible to manufacture every part number which could be created from coding description. Please refer to table of standard part numbers and ask KEMET for other possibilities.*

## Dimensions – Millimeters



Diameter	P	M	W	W1	M1	H1
Ø = 65	22.5	6	13	5	12	12.5
Ø ≥ 75	35	10	25	10	12	16
All dimensions are in mm						

Maximum Driving Torque	
Terminals M6	5 [N*m]
Terminals M10	8 [N*m]
Bolt M12	12 [N*m]

## General Technical Data

Reference Standards	IEC 61071
Dielectric	Polypropylene film
	Non-inductive type winding
Climatic Category	25/70/56 – IEC 60068-1
Maximum hot spot temperature	+75°C
Endurance Test IEC 61071	+65°C @ Case Temperature
Installation	Whatever position
Self extinguish UL94 V0 plastic deck	

## Electrical Characteristics

Rated Voltage	Urms = (see table) VAC
Surge Voltage	Us = (see table) VDC
Capacitance Tolerance	±5% or ±10%
Dissipation Factor PP typical (tgδ0)	≤ 0.0002 at 25°C
Relative Humidity	Annual average ≤ 80% at 24°C
	On 30 days/year permanently 100%. on other days occasionally 90%.
	Dewing not admitted
Capacitance deviation in temperature range (-40 +50°C)	±1.5% maximum on capacitance value at 20°C

## Life Expectancy

Life Expectancy	100,000 hours @ $V_{RMS}$ with $T_{HS} \leq 70^\circ\text{C}$
Capacitance drop at end of life	- 5% (typical)
Failure Rate IEC 61709	See FIT Graph

## Test Methods

Test voltage term to term (Utt)	$1.5 \times V_{RMS}$ for 10 seconds at 25°C
Test voltage term to case (Utc)	3,600 V ~ 50 Hz for 10 seconds
Damp Heat	IEC 60068-2-78
Change of Temperature	IEC 60068-2-14
Vibration Strength	IEC 60068-2-6


**NOTICE:** Care should be taken to ensure that there still is electrical clearance of 15 mm between terminations and other live or earthed parts above the capacitor, in case of safety device activation.

**Table 1 – Ratings & Part Number Reference**


Cap Value ( $\mu$ F)	$V_{rms}$	$U_n$	$U_s$	$dV/dt$ (V/ $\mu$ s)	$I_{rms}$	$ESL <$	$R_s$	$R_{th}$ hs/amb $^{\circ}$ C/W	Case		Part Number
	VAC	VDC	VDC		A	nH	mW		$\varnothing$	H	
100	330	700	1050	12.5	25	100	3.4	8	65	98	C44HLGP6100AASJ
200	330	700	1050	12.5	40	120	1.7	6.1	75	117	C44HLGR6200AASJ
300	330	700	1050	12.5	45	160	1.6	3.6	75	194	C44HLGR6300AASJ
400	330	700	1050	12.5	50	160	2.3	3	75	242	C44HLGR6400AASJ
500	330	700	1050	12.5	55	170	2.1	2.7	75	242	C44HLGR6500AASJ
600	330	700	1050	12.5	65	180	1.9	2.6	85	242	C44HLGR6600AASJ
100	440	1000	1500	20	30	145	4.1	5	75	142	C44HKGR6100AASJ
133	440	1000	1500	20	35	155	3.3	4.5	85	142	C44HKGR6133AASJ
133	440	1000	1500	20	40	170	1.9	4	75	194	C44HKGR6133ZASJ
150	440	1000	1500	20	45	160	1.8	3.8	75	194	C44HKGR6150AASJ
200	440	1000	1500	20	50	175	2.7	3	75	242	C44HKGR6200AASJ
250	440	1000	1500	20	55	190	2.4	2.8	85	242	C44HKGR6250AASJ
Cap Value	VAC	VDC	VDC	$dV/dt$ (V/ $\mu$ s)	$I_{rms}$	ESL	$R_s$	$R_{th}$ hs/amb $^{\circ}$ C/W	Case		Part Number

<sup>1</sup> Maximum admissible RMS current  $T_{HS} \leq 70^{\circ}$ C.

## Lifetime Expectancy/Failure Quota Graphs



V = Operating Voltage [VAC]  
 V<sub>RMS</sub> = Rated Voltage [VAC]



### Example of calculation

Part Number: C44HKGR6100AASJ

Rated V<sub>RMS</sub> = 440 [V<sub>RMS</sub>]

Rated I<sub>RMS</sub> = 30 [A]

R<sub>s</sub> = 4.1 [mΩ]

R<sub>th</sub> = 5.0 [°C/W]

Fundamental Frequency F<sub>1</sub> = 50 [Hz]

Ripple Frequency F<sub>2</sub> = 7000 [Hz]

Fundamental Voltage V<sub>1</sub> = 440 [V~]

Ripple Current I<sub>2</sub> = 27 [A]

T<sub>a</sub> = 35°C

I<sub>1</sub> = I(50) = 2 \* π \* 50 \* 100 \* 10<sup>-6</sup> \* 440 = 13.8 [A]

V<sub>2</sub> = V(7000) = [27 / (2 \* π \* 7000 \* 100 \* 10<sup>-6</sup>)] = 6.14 [V]

### Power Losses and Hot Spot Temperature Calculation

At each frequency, the Power Losses are the sum of:

1. Dielectric Power Losses

$$P_D(f_i) = 2 * \pi * f_i * C * V(f_i)^2 * \text{tg}\delta_0$$

which can be alternatively calculated as

$$P_D(f_i) = \frac{I(f_i)^2}{2 * \pi * f_i * C} * \text{tg}\delta_0$$

where:  $\text{tg}\delta_0 = 2 * 10^{-4}$

2. Joule Power Losses:

$$P_J(f) = R_s * I(f)^2$$

The Total Power Losses are the sum of the components at each frequency:

$$P_T = \sum_i [P_D(f_i) + P_J(f_i)]$$

The Thermal Jump in the Hot Spot is:

$$\Delta T_{HS} = P_T * R_{th-HS}$$

The Hot Spot Temperature is:

$$T_{HS} = T_a + \Delta T_{HS}$$

### Limits for the formulas

The limits listed below should not be exceeded:

$$1. \sqrt{\sum_i V(f_i)^2} \leq V_{RMS}$$

$$2. \sqrt{\sum_i I(f_i)^2} \leq I_{RMS}$$

$$T_{HS} = T_a + \Delta T_{HS} \leq (T_{HS})_{MAX}$$

Where T<sub>a</sub> is the ambient temperature (steady state temperature of the cooling air flowing around the capacitor, measured at 100 mm of distance from the capacitor and at a height of 2/3 height of the capacitor).

3. Maximum case temperature (T<sub>CASE</sub>) ≤ 70°C

$$I_{RMS} = \sqrt{(13.8^2 + 27^2)} = 30 \leq 30 \rightarrow \text{Admitted}$$

$$V_{RMS} = \sqrt{(440^2 + 6.1^2)} = 440 \leq 440 \rightarrow \text{Admitted}$$

$$P_D(50) = 2 * \pi * 50 * 100 * 10^{-6} * 440^2 * 2 * 10^{-4} = 1.22 \text{ [W]}$$

$$P_D(7000) = [27^2 / (2 * \pi * 7000 * 100 * 10^{-6})] * 2 * 10^{-4} = 0.03 \text{ [W]}$$

$$P_J(50) = 3.5 * 10^{-3} * [(2 * \pi * 50 * 100 * 10^{-6} * 440)^2] = 0.67 \text{ [W]}$$

$$P_J(7000) = 3.5 * 10^{-3} * 27^2 = 2.55 \text{ [W]}$$

$$P_T = 1.22 + 0.03 + 0.78 + 3 = 5 \text{ [W]}$$

$$\Delta T_{HS} = 5 * 5 = 25 \text{ [°C]}$$

$$T_{HS} = T_a + \Delta T_{HS}$$

$$T_{HS} = 35 + 25 = 60 \text{ [°C]} \rightarrow \text{OK since hot spot temperature is less than maximum admitted}$$

Expected Life @ T<sub>HS</sub> = 70°C → 100,000 hours (see lifetime curve)

Expected Life @ T<sub>HS</sub> = 60°C → 140,000 hours (see lifetime curve)

## Marking

KEMET	→ Manufacturer Logo
C44HLGR6400AASJ	→ Part Number
400μF ±5%	→ Rated Capacitance and Tolerance
	→ Rated Voltage
Urms=330V~	→ Rated Current and Frequencies
Irms=50A 50/60Hz	→ Climatic Category
SH NO PCBs	→ UL Approvals
	→ Self-Healing Dielectric. UL Logo.
CE B3 12374698	→ CE Logo. Production Date and Batch Number

## Dissipation Factor

Dissipation factor is a complex function involved with the inefficiency of the capacitor. The  $\tan \delta$  may change up and down with increased temperature. For more information, please refer to Performance Characteristics.

## Sealing

### Hermetically Sealed Capacitors

When the temperature increases, the pressure inside the capacitor increases. If the internal pressure is high enough, it can cause a breach in the capacitor which can result in leakage, impregnation, filling fluid or moisture susceptibility.

### Resin Encased/Wrap & Fill Capacitors

The resin seals on resin encased and wrap and fill capacitors will withstand short-term exposure to high humidity environments without degradation. Resins and plastic tapes will form a pseudo-impervious barrier to humidity and chemicals. These case materials are somewhat porous and through osmosis can cause contaminants to enter the capacitor. The second area of contaminated absorption is the lead-wire/resin interface. Since resins cannot bond 100% to tinned wires, there can be a path formed up to the lead wire into the capacitor section. Aqueous cleaning of circuit boards can aggravate this condition.

### Barometric Pressure

The altitude at which hermetically sealed capacitors are operated controls the voltage rating of the capacitor. As the barometric pressure decreases, the susceptibility to terminal arc-over increases. Non-hermetic capacitors can be affected by internal stresses due to pressure changes. This can be in the form of capacitance changes or dielectric arc-over as well as low insulation resistance. Heat transfer can also be affected by altitude operation. Heat generated in operation cannot be dissipated properly and can result in high RI2 losses and eventual failure.

### Radiation

Radiation capabilities of capacitors must be taken into consideration. Electrical degradation in the form of dielectric embitterment can take place causing shorts or opens.

## Environmental Compliance

As an environmentally conscious company, KEMET is working continuously with improvements concerning the environmental effects of both our capacitors and their production.

In Europe (RoHS Directive) and in some other geographical areas like China, legislation has been put in place to prevent the use of some hazardous materials, like Lead (Pb), in electronic equipment. All products in this catalog are produced to help our customers' obligations to guarantee their products to fulfill these legislative requirements. The only material of concern in our products has been Lead (Pb), which has been removed from all designs to fulfill the requirement of containing less than 0.1% of Lead in any homogeneous material.

KEMET will closely follow any changes in legislation world wide and makes any necessary changes in its products, whenever needed. Some customer segments like Medical, Military and Automotive Electronics may still require the use of Lead in electrode coatings. To clarify the situation and distinguish products from each other, a special symbol is used on the packaging labels for RoHS compatible capacitors.

Because of customer requirements there may appear additional markings like LF = Lead Free or LFW = Lead Free Wires on the label.

All KEMET power film products are RoHS Compliant.



RoHS Compliant

---

## Materials & Environment

The selection of materials used by KEMET for the production of capacitors is the result of extensive experience and constant attention to environmental protection. KEMET selects its suppliers according to ISO 9001 standards and carries out statistical analysis on the materials purchased before acceptance. All materials are, to the company's present knowledge, non-toxic and free from Cadmium, Mercury, Chrome and compounds, PCB (Polychlorine Triphenyl), Bromide and Chlorine Dioxins Bromurate Chlorurate, CFC and HCFC and Asbestos.

## Green Products

All KEMET power film products are ROHS Compliant.

## Insulation Resistance

When the capacitor temperature increases, the insulation resistance decreases. This is due to increased electron activity. Low insulation resistance can also be the result of moisture trapped in the windings, caused by a prolonged exposure to excessive humidity.

## KEMET Corporation World Headquarters

2835 KEMET Way  
Simpsonville, SC 29681

Mailing Address:  
P.O. Box 5928  
Greenville, SC 29606

www.kemet.com  
Tel: 864-963-6300  
Fax: 864-963-6521

**Corporate Offices**  
Fort Lauderdale, FL  
Tel: 954-766-2800

## North America

### Southeast

Lake Mary, FL  
Tel: 407-855-8886

### Northeast

Wilmington, MA  
Tel: 978-658-1663

### Central

Novi, MI  
Tel: 248-306-9353

### West

Milpitas, CA  
Tel: 408-433-9950

### Mexico

Guadalajara, Jalisco  
Tel: 52-33-3123-2141

## Europe

### Southern Europe

Paris, France  
Tel: 33-1-4646-1006

Sasso Marconi, Italy  
Tel: 39-051-939111

### Central Europe

Landsberg, Germany  
Tel: 49-8191-3350800

Kamen, Germany  
Tel: 49-2307-438110

### Northern Europe

Bishop's Stortford, United Kingdom  
Tel: 44-1279-460122

Espoo, Finland  
Tel: 358-9-5406-5000

## Asia

### Northeast Asia

Hong Kong  
Tel: 852-2305-1168

Shenzhen, China  
Tel: 86-755-2518-1306

Beijing, China  
Tel: 86-10-5829-1711

Shanghai, China  
Tel: 86-21-6447-0707

Taipei, Taiwan  
Tel: 886-2-27528585

### Southeast Asia

Singapore  
Tel: 65-6586-1900

Penang, Malaysia  
Tel: 60-4-6430200

Bangalore, India  
Tel: 91-806-53-76817

*Note: KEMET reserves the right to modify minor details of internal and external construction at any time in the interest of product improvement. KEMET does not assume any responsibility for infringement that might result from the use of KEMET Capacitors in potential circuit designs. KEMET is a registered trademark of KEMET Electronics Corporation.*



## Prototype Sample Disclaimer

*The Customer acknowledges the following limitations of the prototype samples:*

- (1) Prototype samples are manufactured from preliminary designs and manufacturing processes; may not represent final designs; have not been released for commercial use and are not subject to the same quality control procedures applicable to released products.*
- (2) Prototype samples are not qualified parts and are provided “as-is” by KEMET Electronics Corporation, which specifically disclaims any and all warranties and guarantees, explicit or implied, including, without limitation, the warranties of merchantability and fitness for a particular purpose or use.*
- (3) Prototype samples are not intended for commercial use; are provided for engineering evaluation only and are not recommended for use in the Customer’s production line.*
- (4) The Customer assumes the risk of any and all uses that the Customer makes of the prototype samples.*

## General Disclaimer

*“All product specifications, statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application.*

*KEMET’s product warranty is set forth at [www.kemet.com](http://www.kemet.com) under Terms and Conditions of Sale.”*